



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/00	A2	(11) International Publication Number: WO 99/21375 (43) International Publication Date: 29 April 1999 (29.04.99)									
<p>(21) International Application Number: PCT/SE98/01921</p> <p>(22) International Filing Date: 23 October 1998 (23.10.98)</p> <p>(30) Priority Data:</p> <table border="0"> <tr> <td>9703872-3</td> <td>23 October 1997 (23.10.97)</td> <td>SE</td> </tr> <tr> <td>60/063,024</td> <td>23 October 1997 (23.10.97)</td> <td>US</td> </tr> <tr> <td>09/169,731</td> <td>9 October 1998 (09.10.98)</td> <td>US</td> </tr> </table> <p>(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).</p> <p>(72) Inventors: DAHLMAN, Erik, Bengt, Lennart; Tackjämsvägen 12, S-108 08 Bromma (SE). JAMAL, Karim; Ryttmästarvägen 84, S-162 70 Vällingby (SE).</p> <p>(74) Agent: ERICSSON RADIO SYSTEMS AB; Common Patent Dept., S-164 80 Stockholm (SE).</p>		9703872-3	23 October 1997 (23.10.97)	SE	60/063,024	23 October 1997 (23.10.97)	US	09/169,731	9 October 1998 (09.10.98)	US	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published Without international search report and to be republished upon receipt of that report.</p>
9703872-3	23 October 1997 (23.10.97)	SE									
60/063,024	23 October 1997 (23.10.97)	US									
09/169,731	9 October 1998 (09.10.98)	US									
<p>(54) Title: RANDOM ACCESS IN A MOBILE TELECOMMUNICATIONS SYSTEM</p> <p>(57) Abstract</p> <p>A novel format is provided for an uplink common physical channel in a random access mobile communications system (100), whereby a mobile station (116) transmits a first packet including a predetermined signature pattern (206, 210) in parallel with a second packet including the data part (212, 216, 220) of the random access request. Consequently, in addition to its attendant advantages, the signature part of a random access request can also function as a Pilot by providing additional energy for channel estimation during the data part of the request, while reducing the amount of overhead signalling involved. This additional energy is especially useful for ensuring sufficiently high quality coherent detection of the data part in a rapidly varying radio channel environment.</p>											

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

RANDOM ACCESS IN A MOBILE TELECOMMUNICATIONS SYSTEM

CROSS-REFERENCES TO RELATED APPLICATIONS

5 This Application for Patent claims the benefit of priority from, and hereby incorporates by reference the entire disclosure of, co-pending U.S. Provisional Application for Patent Serial No. 60/063,024, filed October 23, 1997.

 This Application is also related by subject matter to commonly-assigned U.S. Applications for Patent Serial Nos. 08/733,501 and 08/847,655, filed October 18, 1996
10 and April 30, 1997, respectively.

BACKGROUND OF THE INVENTION

Technical Field of the Invention

 The present invention relates generally to the mobile telecommunications field and, in particular, to a method for processing multiple random access mobile-
15 originated calls.

Description of Related Art

 The next generation of mobile communications systems will be required to provide a broad selection of telecommunications services including digital voice, video and data in packet and channel circuit-switched modes. As a result, the number
20 of calls being made is expected to increase significantly, which will result in much higher traffic density on random access channels (RACHs). Unfortunately, this higher traffic density will also result in increased collisions and access failures. Consequently, the new generation of mobile communications systems will have to use much faster and flexible random access procedures, in order to increase their access
25 success rates and reduce their access request processing times.

 In most mobile communications systems, such as, for example, the European joint development referred to as the "Code Division Testbed" (CODIT), and systems operating in accordance with the IS-95 Standard (ANSI J-STD-008), a mobile station can gain access to a base station by first determining that the RACH is available for
30 use. Then, the mobile station transmits a series of access request preambles (e.g., single 1023 chip symbols) with increasing power levels, until the base station detects

- 2 -

the access request. In response, the base station starts the process of controlling the mobile station's transmitted power via a downlink channel. Once the initial "handshaking" between the mobile station and base station has been completed, the mobile user transmits a random access message.

5 In a Spread Spectrum Slot Reservation Multiple Access (SS-SRMA) System, a slotted ALOHA (S-ALOHA) random access scheme is used. At the beginning of a slot, a mobile station will send a random access packet to the base station and then await an acknowledgment from the base station that the packet was received. This S-ALOHA scheme dispenses with a number of steps that characterize the CODIT and
10 IS-95 random access schemes (namely, power ramping and power control).

More specifically, in a CODIT-based Code Division Multiple Access (CDMA) system, a mobile station will attempt to access the base station receiver by using a "power ramping" process that increases the power level of each successive transmitted preamble symbol. As soon as an access request preamble is detected, the base station
15 activates a closed loop power control circuit, which functions to control the mobile station's transmitted power level in order to keep the received signal power from the mobile station at a desired level. The mobile station then transmits its specific access request data. The base station's receiver "despreads" the received (spread spectrum) signals using a matched filter, and diversity-combines the despread signals to take
20 advantage of antenna diversity.

In an IS-95 CDMA system, a similar random access technique is used. However, the primary difference between the CODIT and IS-95 process is that the IS-95 mobile station transmits a complete random access packet instead of just the preamble. If the base station does not acknowledge the access request, the IS-95
25 mobile station re-transmits the access request packet at a higher power level. This process continues until the base station acknowledges the access request.

In a mobile communications system using an S-ALOHA random access scheme, such as the method disclosed in the above-cited U.S. Patent Application Serial No. 08/733,501 (hereinafter, "the '501 Application"), a mobile station generates and
30 transmits a random access packet. A diagram that illustrates a frame structure for such a random access packet is shown in FIGURE 1. The random access packet ("access request data frame") comprises a preamble and a data field portion. The preamble

- 5 -

of use of the remainder of the packet. For all of these reasons, a more flexible random access request procedure was needed to resolve these problems.

The above-cited U.S. Patent Application Serial No. 08/847,655 (hereinafter, the “‘655 Application”) successfully resolved these problems. In accordance with the invention described and claimed in the ‘655 Application, the method assigns each
5 sector in a cell a unique preamble spreading code, and also a unique long-code which is concatenated with the data field’s (signature-associated) short spreading code. The period selected for the long-code can be relatively long in duration (e.g., up to hours or days in length). Consequently, it can be said that the data field of the random
10 access packet is transmitted in a dedicated channel, because no two messages can have the same spreading sequence and phase (unless they have chosen the same signature and transmitted their preambles at the same time).

Also in accordance with the invention in the ‘655 Application, the method sets the widths of the transmission time slots equal to the length of the preamble (minus,
15 for practical purposes, a predefined guard time). Consequently, the mobile station’s random access request can be timed to start at the beginning of the slot, and detected during the preamble period by the matched filter in the base station’s random access receiver. The data field of the mobile station’s random access request is transmitted in the slots succeeding that of the preamble and received by the rake receiver at the
20 base station. However, with that method, subsequent to the preamble period, the matched filter is enabled to receive the preambles of other random access requests made by other mobile stations. Therefore, the matched filter can be utilized continuously and efficiently, and a significantly larger number of random access requests can be processed in comparison with prior random access schemes. As such,
25 the communications throughput and efficiency of a random access system using that method are significantly higher than the throughput and efficiency of prior random access systems.

Nevertheless, other random access problems still exist that need to be solved. For example, FIGURE 6 is a diagram that shows the channel structure for a random
30 access packet (uplink common physical channel message format), which is formatted in accordance with the random access frame structures described earlier. In comparison with the prior approaches, the channel format shown in FIGURE 6

- 6 -

advantageously reduces the number of random access request collisions that can occur, and also simplifies detection of the data field portion of the random access packet. However, a drawback of using this format is that it is not directed to minimizing the amount of overhead signalling involved.

5 Referring to FIGURE 6, in order to be able to coherently detect the data field portion of the random access packet, a certain amount of energy is transmitted in the form of known modulated symbols (denoted as the "Pilot"). The Pilot can be time-multiplexed, I/Q-multiplexed, or code-multiplexed with the data (actually, the type of modulation used is not pertinent to this discussion). The total "overhead" energy of
10 the random access packet is the shaded portion shown in FIGURE 6 (i.e., Preamble plus Pilot). In principle, the Preamble may be used for the same purpose as the Pilot, assuming that a receiver makes a correct decision about the signature transmitted in the Preamble. Consequently, it should be possible to achieve a relatively good radio channel estimate during the Preamble portion of the random access request.

15 However, in a rapidly varying radio channel, the energy used for the channel estimation ideally should be spread out in time over the data field, in order to achieve a radio channel estimate of sufficient quality during that portion of the random access request. Even if a channel estimate of sufficient quality can be achieved during the Preamble (due to the distinctive signature in the Preamble), in a rapidly varying
20 channel, this estimate might not be valid for a significant part of the Data portion of the random access request. As such, it is important to provide enough energy in the Preamble for the receiver to detect the Preamble and correctly identify the channel paths.

On the other hand, in a rapidly varying radio channel, it is also important to
25 provide enough energy in the Pilot to ensure proper coherent detection of the Data portion. Unfortunately, these two important but conflicting energy requirements in an uplink common physical channel format result in the transmission of random access requests with excessive overhead signalling. In other words, the ratio of "overhead" energy (Preamble+Pilot energy) to the "Data" energy is unnecessarily high, with its
30 attendant disadvantages. Nevertheless, as described in detail below, the present invention successfully resolves these problems.

- 7 -

SUMMARY OF THE INVENTION

In accordance with a preferred embodiment of the present invention, a novel format is provided for an uplink common physical channel in a random access mobile communications system, whereby a mobile station transmits a first packet including a predetermined signature pattern in parallel with a second packet including the data portion of the random access request.

An important technical advantage of the present invention is that the signature portion of the random access request can also function as a pilot, by providing additional energy for channel estimation during the data portion of the request.

Another important technical advantage of the present invention is that additional energy is provided with the random access request for ensuring sufficiently high quality coherent detection of the data portion of the request in a rapidly varying radio channel environment.

Yet another important technical advantage of the present invention is that by transmitting the signature portion of a random access request in parallel with the data portion of the request, the amount of overhead signalling is reduced in comparison with prior approaches.

Still another important technical advantage of the present invention is that the overhead energy need not be increased for rapidly varying channels.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be had by reference to the following detailed description when taken in conjunction with the accompanying drawings wherein:

FIGURE 1 is a diagram that illustrates a frame structure for a random access packet;

FIGURE 2 is a block diagram of an apparatus that can be used in a mobile station to generate and transmit the random access packet illustrated in FIGURE 1;

FIGURE 3 is a block diagram of a detection section (for one antenna) of a base station's random access receiver, which functions primarily to estimate the timing of the received signal rays;

FIGURE 4 is a simple block diagram of an accumulator that can be used for the I channel (quadrature detection) in the random access detector section shown in FIGURE 3;

FIGURE 5 is a block diagram of a random access demodulator that can be used to demodulate the data field portion of a random access packet;

FIGURE 6 is a diagram that shows the channel structure for a random access packet (uplink common physical channel message format), which is formatted in accordance with the prior random access frame structures;

FIGURE 7 is a diagram that shows an exemplary format for an uplink common physical channel in a random access communications system, which is structured in accordance with the preferred embodiment of the present invention;

FIGURE 8 is a simple block diagram of an exemplary packet generating apparatus that can be used to implement the preferred embodiment of the present invention; and

FIGURE 9 is a block diagram of a pertinent section of a cellular communications system, which can be used to implement the preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

The preferred embodiment of the present invention and its advantages are best understood by referring to FIGURES 1-9 of the drawings, like numerals being used for like and corresponding parts of the various drawings.

Essentially, in accordance with a preferred embodiment of the present invention, a novel format is provided for an uplink common physical channel in a random access mobile communications system, whereby a mobile station transmits a first packet including a predetermined signature pattern in parallel with a second packet including the data portion of the random access request. Consequently, in addition to its other advantages, the signature portion of a random access request can also function as a Pilot by providing additional energy for channel estimation during the data portion of the request, while reducing the amount of overhead signalling involved. This additional energy is especially useful for ensuring sufficiently high

- 9 -

quality coherent detection of the data portion in a rapidly varying radio channel environment.

Specifically, FIGURE 7 is a diagram that shows an exemplary format for an uplink common physical channel in a random access communications system, which is structured in accordance with the preferred embodiment of the present invention. As shown, the signature portion of the random access request is transmitted in parallel with the data portion of the request. Consequently, the ratio of the energy in the data portion of the request (e.g., in the shaded area shown) to the energy in the overhead (signature) portion is much higher than the data to overhead energy ratio of the channel format shown in FIGURE 6.

FIGURE 8 is a simple block diagram of an exemplary packet generating apparatus that can be used to implement the preferred embodiment of the present invention. In this embodiment, the invention can be implemented as a method and generated to be transmitted on the uplink common physical channel, under the control of a microprocessor located in a mobile station. An example of such a mobile station is shown in FIGURE 9, which is a block diagram of a pertinent section of a cellular communications system that can be used to implement the preferred embodiment of the present invention.

System 100 includes a base station transmit/receive antenna 112 and transmitter/receiver section 114, and a plurality of mobile stations 116 and 118. Although only two mobile stations are shown, FIGURE 9 is for illustrative purposes only, and the present invention can be assumed to include more than two mobile stations. Prior to generating and transmitting an access request frame, a mobile station (e.g., 116) acquires synchronization, or synchronizes, with a target base station receiver (114). The mobile station then determines the starting time for each slot from the base station's broadcast/pilot channel information. The mobile station also retrieves the number of the slot being processed from the broadcast/pilot channel information, which is to be used by the base station to tag its acknowledgment (ACK) message reply with the slot number to ensure that the correct mobile station receives the acknowledgment. More details for synchronizing a mobile station to a base station in a random access environment can be found in the '501 Application.

- 10 -

The target base station also transfers to the requesting mobile station(s) (e.g., over the downlink broadcast channel) each unique random access spreading code and long-code associated with each of the sectors, cells, etc. defined by the base station transceiver. For example, these unique spreading codes and long-codes can be Gold codes or Kasami codes. The mobile station stores the spreading code and long-code information in a memory storage area (not explicitly shown), which is to be retrieved and used by the mobile station to spread the signature fields and data fields of the random access request packets generated. Finally, the base station also transfers to the requesting mobile station(s) (e.g., in an appropriate broadcast message) the signature patterns associated with the signature fields, which can be used to help distinguish between different sectors, cells, etc.

Returning to FIGURE 8, the exemplary apparatus 200 for a mobile station includes a signature generation part 202 and data generation part 204. The signature generation part 202 includes a signal mixer 208, which spreads a "signature i" 206 (e.g., retrieved from the internal memory area in the mobile station) with a specific spreading code 210 for a cell/sector involved (e.g., also retrieved from the internal memory area). Alternatively, the spreading code can be, for example, base station-specific or global in the system involved. The signature generating part 202 thus generates the cell/sector-specific signature part of a random access packet to be transmitted. The signature part's format can be implemented, for example, by spreading the signature field over the entire uplink common physical channel frame, or it can be repeated a number of times within the frame.

The data part of a corresponding random access packet to be transmitted in parallel with the signature part is generated with a data field generator 212. A mixer 214 spreads the generated data field with a unique short spreading code 216 associated with the "signature i". The resulting data field of the corresponding random access packet is then spread with a concatenated code by mixer 218. This concatenated code can be constructed, for example, by a modulo-2 addition (by mixer 218) of the signature-associated short code 216 with a sector-specific long spreading code 220 (e.g., retrieved from internal memory). The length of the resulting data field to be transmitted can be flexibly selected at the mobile station. For this exemplary

- 11 -

embodiment, the spread signature field and spread data field can be multiplexed (e.g., time-multiplexed) in order to be transmitted in parallel from a mobile station.

5 Although a preferred embodiment of the method and apparatus of the present invention has been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiment disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the invention as set forth and defined by the following claims.

- 12 -

WHAT IS CLAIMED IS:

1. A method for transferring data over a direct sequence-code division multiple access physical channel, comprising the steps of:
transmitting a data field including said data over said direct sequence-code
5 division multiple access physical channel during a predefined duration; and
simultaneously transmitting a signature field over said direct sequence-code
division multiple access physical channel during said predefined duration, a signature
included in said signature field spread by a first predetermined code, and said data
included in said data field spread by a second code associated with said signature.
- 10 2. The method of Claim 1, wherein said data field and said signature field
are transmitted in parallel.
3. The method of Claim 1, wherein a length of said signature field is set
substantially equal to a width of a transmission slot.
4. The method of Claim 1, wherein a length of said data field is
15 selectively varied.
5. The method of Claim 1, wherein said signature field comprises at least
one of a plurality of signature patterns.
6. The method of Claim 1, wherein said direct sequence-code division
multiple access physical channel comprises an uplink common physical channel.
- 20 7. A signal format for use in transmitting a random access request in a
mobile communications system, comprising:
a data field; and
a signature field transmitted in parallel with said data field, said signature field
including a signature spread by a first predetermined code, and said data field
25 including information data spread by a second code associated with said signature.

- 13 -

8. The signal format of Claim 7, said information data further spread with a sector-associated long spreading code.

9. A method of transmitting data on a DS-CDMA common physical channel, comprising the steps of:

5 transmitting a data part of a signal; and
transmitting a signature part of said signal in parallel with said data part, wherein said signature part is spread by a predetermined code, and said data part is spread by a code associated with said signature part.

10 10. The method of Claim 9, wherein said signature part is selected from a predetermined set including at least one signature.

11. The method of Claim 10, wherein said predetermined set comprises an orthogonal set.

12. The method of Claim 9, wherein said data part and said signature part are scrambled by a predetermined scrambling code.

15 13. The method of Claim 9, further comprising the step of transmitting said signature part and said data part from a mobile station.

14. The method of Claim 13, wherein said signature part further comprises a pilot signal.




20 15. An apparatus for use in generating a DS-CDMA common physical channel, comprising:

means for generating a signature code;
means for spreading said signature code with a spreading code associated with a predetermined sector or cell;
means for generating a data field; and

- 14 -

means for spreading said data field with a code associated with said signature code.

16. The apparatus of Claim 15, further comprising means for transmitting said spread signature code in parallel with said spread data field.

*FIG. 1**FIG. 2**FIG. 3*




FIG. 4




FIG. 5




FIG. 6






FIG. 7

3/3


**FIG. 8****FIG. 9**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/38, H04B 7/26		A3	(11) International Publication Number: WO 99/21375
			(43) International Publication Date: 29 April 1999 (29.04.99)
(21) International Application Number: PCT/SE98/01921		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 October 1998 (23.10.98)		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(30) Priority Data: 9703872-3 23 October 1997 (23.10.97) SE 60/063,024 23 October 1997 (23.10.97) US 09/169,731 9 October 1998 (09.10.98) US			
(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).			
(72) Inventors: DAHLMAN, Erik, Bengt, Lennart; Tackjämsvägen 12, S-108 08 Bromma (SE). JAMAL, Karim; Ryttnästarvägen 84, S-162 70 Vällingby (SE).			
(74) Agent: ERICSSON RADIO SYSTEMS AB; Common Patent Dept., S-164 80 Stockholm (SE).		(88) Date of publication of the international search report: 19 August 1999 (19.08.99)	

(54) Title: RANDOM ACCESS IN A MOBILE TELECOMMUNICATIONS SYSTEM



(57) Abstract

A novel format is provided for an uplink common physical channel in a random access mobile communications system, whereby a mobile station transmits a first packet including a predetermined signature pattern (206, 210) in parallel with a second packet including the data part (212, 216, 220) of the random access request. Consequently, in addition to its attendant advantages, the signature part of a random access request can also function as a Pilot by providing additional energy for channel estimation during the data part of the request, while reducing the amount of overhead signalling involved. This additional energy is especially useful for ensuring sufficiently high quality coherent detection of the data part in a rapidly varying radio channel environment.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

Interr 1st Application No

PCT/SE 98/01921

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04Q7/38 H04B7/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	WO 98 23047 A (ERICSSON TELEFON AB L M) 28 May 1998 see abstract; claim 1; figures 1,3 ---	1-16
A	WO 97 05708 A (ERICSSON GE MOBILE INC) 13 February 1997 see abstract; claims 1-3 ---	1-16
A	EP 0 765 096 A (NIPPON TELEGRAPH & TELEPHONE) 26 March 1997 see abstract; claim 1 -----	1-16

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

21 June 1999

Date of mailing of the international search report

01/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Harris, E

INTERNATIONAL SEARCH REPORT

Internat'l Application No

PCT/SE 98/01921

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9823047 A	28-05-1998	AU 5073498 A	10-06-1998
WO 9705708 A	13-02-1997	US 5615209 A	25-03-1997
		AU 6494896 A	26-02-1997
		CA 2227880 A	13-02-1997
		CN 1196842 A	21-10-1998
		EP 0840960 A	13-05-1998
EP 0765096 A	26-03-1997	JP 9093646 A	04-04-1997
		CN 1159110 A	10-09-1997
		JP 9233051 A	05-09-1997